

## TECHNICAL INFORMATION - FLOW RATES

Wessex shower valves  
 Concealed inline two function shower valve | SV6605



### TOP OUTLET ONLY

Inlet Pressure	0.1	0.2	0.3	0.4	0.5	1	2	3
(Bar) Outlet Pressure	0.08	0.15	0.23	0.31	0.38	0.99	1.96	2.94
(Litres/Minute) Flow Rate	5.20	7.70	9.20	10.90	12.10	21.00	21.60	36.40

### BOTH OUTLETS OPEN - TOP

Inlet Pressure	0.1	0.2	0.3	0.4	0.5	1	2	3
(Bar) Outlet Pressure	0.10	0.20	0.30	0.39	0.48	0.99	1.97	2.96
(Litres/Minute) Flow Rate	0	0	3.60	4.28	5.20	11.40	19.00	22.90

### BOTH OUTLETS OPEN - BOTTOM

Inlet Pressure	0.1	0.2	0.3	0.4	0.5	1	2	3
(Bar) Outlet Pressure	0.09	0.19	0.29	0.39	0.50	0.99	1.99	2.99
(Litres/Minute) Flow Rate	7.40	10.20	12.30	14.90	15.70	23.80	33.60	41.90

### BOTTOM OUTLET ONLY

Inlet Pressure	0.1	0.2	0.3	0.4	0.5	1	2	3
(Bar) Outlet Pressure	0.09	0.19	0.30	0.40	0.50	0.95	1.91	2.86
(Litres/Minute) Flow Rate	7.00	9.40	11.30	13.00	14.40	20.50	29.50	35.90